

HYDRAULIC EXTERNAL PIPE CLAMPS

Our Hydraulic External Pipe Clamps have a wide gap, which allows the welding of the root up to 90% before removing the clamp. Edge misalignment can be eliminated by means of jackscrews or a wedge which is placed under the alignment bridge. The air gap can be adjusted by means of chisel. The hydraulic cylinder, which is available as an option, operates in all positions and can be used for all pipe diameters.

The external line-up clamp is available in a medium, heavy and heavy-duty version for pipes from 12-80 inch diameter.

Hydraulic External Pipe Clamps - Medium

Pipe range: 12" - 80" (324 - 2020 mm)



Part.-No.	Nom. Pipe Size		OD mm	OD inch
	mm DN	Inches		
11 001 0323	300	12	323,8	12.8
11 001 0355	350	14	355,6	14.0
11 001 0406	400	16	406,4	16.0
11 001 0457	450	18	457,0	18.0
11 001 0508	500	20	508,0	20.0
11 001 0610	600	24	610,0	24.0
11 001 0711	700	28	711,0	28.0
11 001 0762	750	30	762,0	30.0
11 001 0813	800	32	813,0	32.0
11 001 0864	850	34	864,0	34.0
11 001 0914	900	36	914,0	36.0
11 001 1016	1000	40	1016,0	40.0
11 001 1067	1050	42	1067,0	42.0
11 001 1118	1100	44	1118,0	44.0
11 001 1120	1200	48	1219,0	48.0
11 001 1320	1300	52	1321,0	52.0
11 001 1420	1400	56	1422,0	56.0
11 001 1520	1500	60	1524,0	60.0
11 001 1620	1600	64	1626,0	64.0
11 001 1720	1700	68	1727,0	68.0
11 001 1820	1800	72	1829,0	72.0
11 001 2020	2000	80	2032,0	80.0