

Hydraulic External Pipe Clamp - Heavy

Pipe range: 16" - 64" (407 - 1620 mm)

- The hydraulic cylinder works in vertical position and can be exchanged easily, if necessary. The alignment bridges have a widegap, allowing to weld the root up to 90% before removing the clamp. Hydraulic jack 10 t. For gas pipelines (fine-grained steel) and for thick-walled pipes made of sturdy flat steel.

Part.-No.	Nom. Pipe Size		OD mm	OD inch
	mm DN	Inches		
11 SK1 0406	400	16	406,4	16.0
11 SK1 0457	450	18	457,0	18.0
11 SK1 0508	500	20	508,0	20.0
11 SK1 0610	600	24	610,0	24.0
11 SK1 0711	700	28	711,0	28.0
11 SK1 0762	750	30	762,0	30.0
11 SK1 0813	800	32	813,0	32.0
11 SK1 0864	850	34	864,0	34.0
11 SK1 0914	900	36	914,0	36.0
11 SK1 1016	1000	40	1016,0	40.0
11 SK1 1067	1050	42	1067,0	42.0
11 SK1 1118	1100	44	1118,0	44.0
11 SK1 1220	1200	48	1219,0	48.0
11 SK1 1320	1300	52	1321,0	52.0
11 SK1 1420	1400	56	1422,0	56.0
11 SK1 1520	1500	60	1524,0	60.0
11 SK1 1620	1600	64	1626,0	64.0



The hydraulic cylinder for our external pipe clamps works in every position and is suitable for all pipe diameters. The weight of this special cylinder is only 15,3 kg.

Hydraulic Cylinder

Suitable for all diameters

